

Nilfisk-ALTO TRUCK BOOSTER — WHY COMPROMISE

Efficient outdoor cleaning of vehicle fleets

Nilfisk
ALTO
Why Compromise



Wap
KEW

TECHNOLOGIES



TRUCK BOOSTER


- Efficient outdoor cleaning of vehicle fleets

The Nilfisk-ALTO TRUCK BOOSTER is the ideal outdoor stationary pressure washer for use in haulage companies, fleet parks or for cleaning of animal transport vehicles near slaughterhouses.

Simply placed in the vehicle park or forecourt, the Nilfisk-ALTO TRUCK BOOSTER offers simple, efficient and cost effective cleaning – all year round.

EcoPower

High Performance



Low running costs

- EcoPower boiler reduces fuel consumption costs by up to 18%

- EcoPower boiler and overall serviceability concept reduces maintenance time

ErgoSystem

Applied Ergonomics

Ergonomics

- Easy to use control box with pre-set temperatures and flow.
- Low noise level thanks to 1450 rpm motor-pump unit



▲ Stainless steel design – easy to clean, rust-free

▲ Easy access to all components for service

Durability

Reliability

- Reinforced and tested NP5 and C3 motor pump units – long working life due to 1450 rpm motor, reinforced pump head and ceramic pistons
- Internal heater, cabinet insulation protect the unit during cold weather.
- Stainless steel frame and cabinet protect against corrosion

Quality Cleaning

- ideal truck cleaning performances
- temperatures up to 90 C at high flow for removal of traffic film, oils, grease and pollution
- steam stage for very intense cleaning applications
- choice of up to 2 cleaning detergents

Technical data:	TRUCK BOOSTER 7-63D	TRUCK BOOSTER 5-49D
Pressure	bar/MPa 175/17.5	170/17
Cleaning impact	kg/Force 6.3	4.9
Water Flow, Qmax., Qrec	l/hr 1260/1170	970/930
Water Flow, min.	l/hr 400	400
Max. inlet temp.	°C 40	40
Water temp (water/steam)°C	100/140	90/140
Power consumed	kW 8.3	6.9
	V/~ /Hz/A 400/3/50/15.8	400/3/50/13.9
	230-400/3/50/25	
Pump	RPM 1450	1450
Fuel tank	l 33	33
Fuel consumption (ΔT=45°C)*kg/h	5.6	4.3
Space for detergent tanks	2 x 25 l	2 x 25 l
Sound level- LpA	dBa 76	75.5
Weight	kg 285	275
Dimensions (L x W x H)mm	1670 x 1025 x 715	1670 x 1025 x 715
HP Hose	m/ø 10/DN 10	10/DN 10
Standard accessories:		
Ergo 3000 Gun	106402190	106402190
Ergo 3000 Lance	Tornado	Tornado
Tornado Plus Nozzle	0680	0550
Ceramic pistons	●	●
Internal heating system	●	●
WDK detergent system	●	●
Remote control box 107370973	○	○
Article No.	107370810 (EU) 107370820 (NO)	107370830 (EU)

No claims can be made on the basis of information or illustrations contained in this catalogue. Subject to alteration of technical data, design and equipment.

Dealer:

Nilfisk ALTO

www.alto-online.com